



Bartovation LLC.  
2483 47th St.  
Astoria NY 11103  
contact@bartovation.com

## **Product Technical Fact Sheet**

Product Code: PPA02V50

Product Description: High-level Peracetic Acid Test Strips, 0-1000 ppm

Application: The high level PAA test strip is used for testing sanitization and disinfecting levels of peracetic acid in water.

Test Range: 0-1000 ppm

Test Increments: Color chart calibrated at 0, 100, 250, 500, and 1000 ppm

Accuracy: +/- 1/2 color chart unit

Detection Limit: 50 ppm

Storage Recommendations: Store in original packaging in a cool (20-30C), dry, place out of direct sunlight.

Shelf-Life: Two years from date of manufacture when stored properly in original packaging.

Interferences: Test strip may react to other oxidizing materials, chlorine, peroxide, etc.

Instructions for Use:

1. Remove one test strip from the vial, being careful not to touch the test pad with your fingers.
2. Dip the test strip into the solution to be tested for 2 seconds.
3. Remove and shake off any excess liquid.
4. Compare the test pad to the color chart after 10 seconds.

Chemistry Behind the Test: The test pad is treated with a formula consisting of buffers, surfactants, and red-ox indicators. The presence of peracetic acid in a sample causes the red-ox indicator in the test pad to develop color. The intensity of the color developed is proportional to the amount of peracetic acid present.

Other information: Peracetic acid is typically sold in a concentrated formula consisting of peracetic acid, hydrogen peroxide, acetic acid, and water. The low level PAA strips were developed to work with solutions made from these concentrates.

Disclaimer: These test strips are not intended for use to diagnose, treat, or monitor any medical condition.